



AOB
Laboratuvar ve Kalite kontrol

21. YIL
2005 – 2026

BOYA LABORATUVAR VE KALİTE KONTROL TEST SİSTEMLERİ

PAINT LABORATORY TEST EQUIPMENTS

PULL-OFF ADHESION TESTER

This instrument is a portable adhesion tester that uses the hydraulic pulling force of an adhesion tester to peel the coating per unit area off the coating substrate. Suitable for use in laboratories and factories, with readings displayed in Psi and MPa units on a LCD screen, with a measurement range of 0-3000psi. Adhesion strength, waterproof and dustproof advantages, and equipped with a high-quality 1.5 meter long hose that can be used to measure narrow areas.



Standard: GB/T 5210; ISO 4624,16276-1;ASTM D 4541,D7234

TECHNICAL PARAMETER

Instrument Type	Manual type
Spindle Specifications	Standard configuration: 20 mm (optional configuration: 10 mm/14 mm/50 mm)
Resolving Power	1 psi (0.01 MPa)
Accuracy	± 1% FSR
Range	100-3000 psi (0.7-20 MPa)
Typical Applications	Metal coating
Display Screen	LCD
Source	Rechargeable lithium batteries
Data Interface	USB

ORDER NUMBER

AOB-PSH-2658
Pull-Off Adhesion Tester

SHIPPING LIST

Instrument host,
data cable,
spindle set,
sleeve cutter,
3M adhesive,
user manual



www.aobstore.com.tr



info@aoblab.com